

AD No. 33 037
ASTIA FILE COPY

OREGON STATE COLLEGE

ONR Contract Nonr - 974 (00)

NR-019-130

Technical Report No. 1

THEORY OF THE ELEMENTARY PROCESSES
IN THE SPECTROPHONE

By

J. C. DECIUS

Department of Chemistry
Oregon State College
Corvallis, Oregon

15 June 1954

THIS REPORT HAS BEEN DELIMITED
AND CLEARED FOR PUBLIC RELEASE
UNDER DOD DIRECTIVE 5200.20 AND
NO RESTRICTIONS ARE IMPOSED UPON
ITS USE AND DISCLOSURE.

DISTRIBUTION STATEMENT A

APPROVED FOR PUBLIC RELEASE;
DISTRIBUTION UNLIMITED.

I. THEORY OF THE ELEMENTARY PROCESSES IN

THE SPECTROPHONE

A. INTRODUCTION

The use of the infrared spectrophone for the determination of the lifetime of vibrationally excited molecules was first described by Slobodskaya (1). This instrument consists essentially of a cell containing an infrared absorbing gas; the cell is illuminated intermittently with radiation corresponding to an absorption band of the gas and the periodic variations in pressure due to alternate heating and cooling are detected with a sensitive microphone. Changes in phase shift of this signal, relative to the phase of the radiation, are related to the mean vibrational lifetime of the excited molecules. The experiments of Slobodskaya were performed with various mixtures of CO_2 and air, and results were reported for both infrared fundamentals ($\omega_2 = 667 \text{ cm}^{-1}$ and $\omega_3 = 2350 \text{ cm}^{-1}$) as well as a combination band.

An analysis of this experiment was described by Stepanov and Girin (2), who considered a two state model of the vibrational levels and assumed square wave excitation.

A detailed analysis of the inelastic collision process in which vibrational energy is converted into translational energy has been given by Schwartz, Slawsky, and Herzfeld (3), whose results indicate that the probability of this sort of process is a very sensitive function of both the energy of the vibrational quantum and of the reduced mass of the collision. At room temperature and atmospheric pressure, the relaxation time for this process may vary from the order of the 10^{-6} sec. for vibrational modes of relatively low frequency, to as high as 1 sec. for

the higher frequency modes. Relaxation times as large as the latter figure have not been observed for several reasons: in sound dispersion studies, for example, the equilibrium heat capacity due to such modes is too small to detect.

It is the purpose of the remainder of this paper to carry out an analysis of the rates of the elementary processes occurring in the spectrophone with emphasis upon the fact that the large range of the parameters, especially their sensitivity to the vibrational frequency, leads to complications in the interpretation of the observed phase shifts.

B. RATE OF CONVERSION OF RADIANT TO TRANSLATION ENERGY

It has been shown by Schwartz, Slawsky, and Herzfeld (3) that the net rate of conversion translational into vibrational energy is

$$\frac{dE_v}{dt} = \frac{1}{\tau} [E_v(T) - E_v] \quad (1)$$

where τ is a characteristic time constant measuring the life-expectancy of the excited vibrational state before its termination by an inelastic collision. E_v is the actual vibrational energy and $E_v(T)$ is the vibrational energy which would be in equilibrium with the translational energy at translational temperature, T .

The net rate of absorption of photons must now be considered. For this purpose, the Einstein coefficients are required, namely $A_{v \rightarrow v-1}$, $B_{v \rightarrow v-1}$, and $B_{v \rightarrow v+1}$, which are respectively the coefficients of spontaneous emission, induced emission, and induced absorption. Only the fundamental transitions involving unit change in the vibrational quantum number, v , are considered. These quantities are given by the following expressions,

$$A_{v \rightarrow v-1} = \frac{8\pi^2 \nu^2}{3c^3} \left(\frac{\partial f}{\partial \nu} \right) = \alpha \nu \quad (2a)$$

$$B_{v \rightarrow v-1} = \frac{\pi}{3h\nu} \left(\frac{\partial \mu}{\partial Q} \right)^2_v = \beta_v \quad (2b)$$

$$B_{v \rightarrow v+1} = \frac{\pi}{3h\nu} \left(\frac{\partial \mu}{\partial Q} \right)^2_{(v+1)} = \beta_{(v+1)} \quad (2c)$$

in the case of the harmonic oscillator. The dipole derivative with respect to the normal coordinate, Q , is evaluated at equilibrium and it is assumed that only linear terms in Q appear in the expansion of μ . Now if the number of molecules per unit volume in the vibrational state v is indicated by n_v and if ρ is the density of radiation of appropriate frequency, the net rate of increase of vibrational energy, per unit volume, at the expense of radiation is

$$\begin{aligned} \frac{dE_v}{dt} &= h\nu \sum_{v=0}^{\infty} \left[- (A_{v \rightarrow v-1} + B_{v \rightarrow v-1} \rho) + B_{v \rightarrow v+1} \rho \right] n_v \\ &= h\nu \left(-\alpha \sum_v v n_v + \beta \rho \sum_v n_v \right) \\ &= h\nu \left[-\alpha \left(\frac{E_v}{h\nu} - \frac{n}{2} \right) + \beta \rho n \right] = -\alpha E_v + h\nu \left(\frac{\alpha}{2} + \beta \rho \right) n \quad (3) \end{aligned}$$

In (3), n is the total number of molecules per unit volume.

In the spectrophone experiments to be considered, the radiation density, ρ , is modulated with angular frequency, ω , so that

$$\rho = \rho_0 + \rho_1 \sin \omega t + \rho_2 \sin 2\omega t + \dots \quad (4)$$

Although in some cases the wave form may be more nearly square than sinusoidal, the detecting device is usually sharply tuned to the fundamental modulation frequency, so that we shall be primarily concerned

with the second term in (4), and will only use the first two terms in the following development.

By combining the expressions for interconversion of translational and vibrational energy and for interconversion of vibrational and radiant energy, using the modulation frequency, ω , one finds

$$\frac{dE_v}{dt} = -\left(\alpha + \frac{1}{\tau}\right)E_v + \frac{1}{\tau}E_v(T) + a_0 + a_1 \sin \omega t \quad (5)$$

$$\text{where } a_0 = nh\nu \left(\frac{N}{2} + \beta \phi_0 \right) \quad (5a)$$

$$a_1 = nh\nu \beta \phi_1 \quad (5b)$$

If one now considers the gross heat balance in the spectrophone cell, and allows for heat loss only by conduction, the heat flow equation becomes

$$\kappa \nabla^2 T - c_v \frac{\partial T}{\partial t} + \frac{1}{\tau} [E_v - E_v(T)] = 0 \quad (6)$$

in which κ is the thermal conductivity, c_v the heat capacity (for unit volume), and the last term represents the rate of production of sensible heat by conversion of vibrational into translation energy. The simultaneous solution of (5) and (6) is considerably simplified in case $h\nu \gg kT$, since $E_v(T)$ reduces to the zero point energy, $nh\nu/2$, i.e., a constant independent of temperature and hence of the time. Subject to such an assumption, the steady-state solution of (5) is given by:

$$E_v = b_0 + b_1 \sin(\omega t + \phi) \quad (7)$$

with
$$b_0 = \frac{nh\nu \left[\frac{1}{2}(\alpha\tau + 1) + \beta\tau\phi_0 \right]}{\alpha\tau + 1} \quad (7a)$$

$$b_1 = \frac{nh\nu \beta\tau\phi_1}{[(\omega\tau)^2 + (\alpha\tau + 1)^2]^{1/2}} \quad (7b)$$

$$= \tan^{-1} \left\{ \frac{-\omega\tau}{\alpha\tau + 1} \right\} \quad (7c)$$

Before proceeding to a discussion of the heat flow equation, we must consider the case in which $E_v(T)$ cannot be put equal to $nh\nu/2$. Since the actual variations of T are small,

$$E_v(T) = c_v' \Delta T + E_v(T_0)$$

where c_v' is the vibrational heat capacity per unit volume and at constant volume, and $T = T_0 + \Delta T$. Equations (5) and (6) are replaced by

$$\frac{dE_v}{dt} = -(\alpha + \frac{1}{\tau}) E_v + \frac{c_v'}{\tau} \Delta T + \frac{E_v(T_0)}{\tau} + a_0 + a_1 \sin \omega t \quad (5')$$

$$K \nabla^2 (\Delta T) - c_v \frac{\partial \Delta T}{\partial t} + \frac{E_v}{\tau} - \frac{c_v'}{\tau} \Delta T - \frac{E_v(T_0)}{\tau} = 0 \quad (6')$$

A formal solution of (5') is obtained by putting

$$E_v = b_0' + b_1 \sin(\omega t + \phi) + \frac{c_v'}{\tau} \int \Delta T dt$$

with
$$b_0' = \frac{E_v(T_0) + nh\nu \left(\frac{\alpha\tau}{2} + \beta\tau\phi_0 \right)}{\alpha\tau + 1}$$

C. SOLUTION OF THE HEAT FLOW EQUATION

First consider the case in which $E_v(T)$ is a constant, namely $nh\nu/2$.

The heat conduction equation (6) then becomes

$$\kappa \nabla^2 T - c_v \frac{\partial T}{\partial t} + \frac{b_0}{\tau} + \frac{b_1}{\tau} \sin(\omega t + \phi) = 0 \quad (8)$$

with the aid of (7). Again, we are interested in the steady-state, periodic solution of (8). Although various boundary values may be assumed, we shall consider only the simple one-dimensional problem, $T = T(x, t)$ with $T(0, t) = T(\ell, t) = 0$, ℓ representing the length of the cell. The assumption of a solution of the form

$$T(x, t) = f(x) + g(x) \sin(\omega t + \phi) + h(x) \cos(\omega t + \phi) \quad (9)$$

together with the above boundary conditions leads to rather clumsy expressions for g and h involving linear combinations of the functions

$$\frac{\sinh x}{\lambda} \frac{\sin x}{\lambda}, \frac{\sinh x}{\lambda} \frac{\cos x}{\lambda}, \text{ and } \cosh \frac{x}{\lambda} \sin \frac{x}{\lambda}, \text{ where}$$

$$\lambda^2 = \frac{2\kappa}{\omega c_v} \quad (10)$$

The average values of $g(x)$ and $h(x)$ over the length of the cell, simplify somewhat to yield the following expressions:

$$\bar{g} = \frac{-b_1}{\omega \tau c_v} \left(\frac{\lambda}{\ell} \right) \left[\frac{\sinh \frac{\ell}{\lambda} \cos \frac{\ell}{\lambda} + \cosh \frac{\ell}{\lambda} \sin \frac{\ell}{\lambda} - \sinh \frac{\ell}{\lambda} \cosh \frac{\ell}{\lambda} - \sin \frac{\ell}{\lambda} \cos \frac{\ell}{\lambda}}{\sinh^2 \frac{\ell}{\lambda} + \sin^2 \frac{\ell}{\lambda}} \right] \quad (11)$$

$$\bar{h} = \frac{b_1}{\omega \tau c_v} \left(\frac{\lambda}{\ell} \right) \left[\frac{\sinh \frac{\ell}{\lambda} \cosh \frac{\ell}{\lambda} - \sinh \frac{\ell}{\lambda} \cos \frac{\ell}{\lambda} + \cosh \frac{\ell}{\lambda} \sin \frac{\ell}{\lambda} - \sin \frac{\ell}{\lambda} \cos \frac{\ell}{\lambda}}{\sinh^2 \frac{\ell}{\lambda} + \sin^2 \frac{\ell}{\lambda}} - \frac{\ell}{\lambda} \right] \quad (12)$$

If the condition $\ell \gg \lambda$ obtains, the expressions for \bar{g} and \bar{h} simplify to

$$\bar{g} \rightarrow \frac{b_1}{\omega \tau c_v} \frac{\lambda}{\ell}, \quad \bar{h} \rightarrow \frac{b_1}{\omega \tau c_v} \left(\frac{\lambda}{\ell} - 1 \right)$$

whence it follows that the time dependent part of T , averaged over the cell length, is

$$\bar{T} = \frac{b_1}{\omega \tau c_v} \left[\frac{\lambda}{\ell} \sin(\omega t + \phi) + \left(\frac{\lambda}{\ell} - 1 \right) \cos(\omega t + \phi) \right] \quad (13)$$

which may finally be written in the form

$$\bar{T} = \frac{b_1}{\omega \tau c_v} \left(1 - 2\frac{\lambda}{\ell} + \frac{2\lambda^2}{\ell^2} \right)^{1/2} \sin(\omega t + \phi + \phi') \quad (14)$$

$$\phi = \tan^{-1} \left(1 - \frac{\ell}{\lambda} \right) \quad (15)$$

It is apparent that when $\ell \gg \lambda$, ϕ' will be very close to $-\pi/2$, and although λ may vary slightly if the pressure or composition of the gas in the spectrophone cell is altered, ϕ' will remain almost constant.

Turning to the case in which $E_v(T)$ is not constant, we shall neglect the dependence of phase shift upon heat conduction, which is simply equivalent to letting $K \rightarrow 0$ in (8). In such a case, the functions g and h assume the values:

$$g = \frac{\omega^2 \tau^2 \gamma b_1}{c_v [(\gamma - \omega^2 \tau^2)^2 + \omega^2 \tau^2 \gamma^2]} \quad (16)$$

$$h = \frac{(\gamma - \omega^2 \tau^2) \omega \tau b_1}{c_v [(\gamma - \omega^2 \tau^2)^2 + \omega^2 \tau^2 \gamma^2]} \quad (17)$$

in which $\gamma = c_v'/c_v$, i.e., the ratio of the vibrational heat capacity to

the translational heat capacity. Here the phase shift turns out to be

$$\phi'' = \tan^{-1} \left\{ \frac{\gamma - \omega^2 \tau^2}{\omega \tau \gamma} \right\}$$

Continuing the assumption that ω is high enough so that heat conduction does not play an important role, we now combine the results of (7), (7b), (7c), (16), and (17) to obtain an expression which gives the temperature amplitude and the overall phase shift:

$$\Delta T = \Delta T_1 \sin(\omega t + \phi)$$

in which

$$\begin{aligned} \Delta T_1 &= \frac{\omega \tau n h \nu \beta \tau \rho_1}{C_v} \left[(\gamma - \omega^2 \tau^2)^2 + (\omega \tau \gamma)^2 \right]^{-1/2} \left[(\omega \tau)^2 + (\alpha \tau + 1)^2 \right]^{-1/2} \\ &= \frac{\omega \tau^2}{C_v} A^* I_1 \left[(\gamma - \omega^2 \tau^2)^2 + (\omega \tau \gamma)^2 \right]^{-1/2} \left[(\omega \tau)^2 + (\alpha \tau + 1)^2 \right]^{-1/2} \end{aligned} \quad (19)$$

and

$$\phi = \tan^{-1} \left\{ \frac{-\omega^2 \tau^2 \gamma + (\alpha \tau + 1)(\gamma - \omega^2 \tau^2)}{\omega \tau [\gamma - \omega^2 \tau^2 + (\alpha \tau + 1) \gamma]} \right\} \quad (20)$$

Here the integrated absorption coefficient, A^* , at the gas density employed, has been introduced; see Thorndike, Wells, and Wilson (5).

I_1 is the intensity of the modulated radiation.

Some simplification of (20) is greatly desirable in order to relate the observed phase shift to τ . Other factors being equal, a small value of $\alpha \tau$ in comparison with unity leads to a large amplitude and to the following simplification of (20). If $\alpha \tau \ll 1$ and if $\omega^2 \tau^2 < \gamma$, (20) becomes approximately

$$\phi \approx \tan^{-1} \frac{1}{2\omega\tau} \approx \frac{\pi}{2} - 2\omega\tau$$

since $\omega\tau$ is then necessarily small compared with unity. This situation is realized experimentally for lower frequency molecular modes, say below 1000 cm^{-1} , where τ is less than 10^{-4} sec , $\gamma \approx 0.1$, with appropriate choice of ω .

For the higher frequency molecular modes, say above 2000 cm^{-1} , τ may become quite large, perhaps 10^{-2} seconds or greater. Using Eggers and Crawford's (4) value of $\frac{\partial \mu}{\partial Q}$ for the stretching mode of CO_2 , $\alpha\tau$ would be 42.7 with $\tau = 10^{-2}$ sec. Thus, for high frequency molecular modes of high intensity, we may perhaps need to consider the case in which $\alpha\tau \gg 1$, which simplifies ϕ to

$$\phi \approx \tan^{-1} \frac{1}{\omega\tau} \approx \frac{\pi}{2} - \omega\tau$$

provided $\omega\tau \ll 1$. This latter situation is relatively unfavorable, however, for the following reasons: (i) when τ is large, a very small ω must be employed to justify the simplification of \tan^{-1} just employed; (ii) this leads to relatively large conduction heat loss. In any case, it appears that Slobodskaya's (1) identification of the observed time lag with τ is not justified for the 2350 cm^{-1} band of CO_2 when a modulation frequency of $\omega = 1572\text{ sec}^{-1}$ was employed.

D. CONCLUSION

It has been shown that the phase shift of the temperature variations in the spectrophone cell, averaged over the length of the cell, depends in a complex manner upon the following variables:

α = probability of spontaneous emission

γ = ratio of vibrational to translational heat capacity

ω = modulation frequency

τ = mean lifetime for inelastic collisions.

Although α and γ are known with good accuracy for the modes of vibration to be studied experimentally, it appears necessary to work under conditions such that the observed phase shift is simply related to τ :

this situation is attained experimentally most easily for low frequency molecular modes, e.g., less than 1000 cm^{-1} , or for higher frequencies in the case of collisions with very light molecules such as H_2 or He . It is further necessary that $\omega^2 \tau^2 \lesssim \gamma$. Since γ is 0.133 when the molecular frequency is 1000 cm^{-1} , and τ may be of the order 10^{-4} , ω should be less than 10^2 .

When $\alpha \tau$ is much less than unity, and, in addition, $\omega^2 \tau^2 < \gamma$ the amplitude of the temperature variations reduces to

$$\Delta T_1 = \frac{\alpha \tau^2 A^* I_1}{\gamma C_V}$$

and when $\alpha \tau \ll 1$, but $\omega^2 \tau^2 \gg \gamma$

$$\Delta T_1 = \frac{A^* I_1}{\omega^2 \tau C_V}$$

It is thus apparent that optimum response is obtained when $\omega \tau$ is of the order of $\gamma^{1/2}$, a condition which is somewhat in conflict with the optimum situation for a simple relation between ϕ and τ . If γ vanishes, the response improves as ω decreases, but this conclusion, of course, neglects the effect of heat conduction, which demands that

$$\omega \gg \frac{2K}{\ell^2 C_V}$$

for good response.

E. BIBLIOGRAPHY

- (1) P. V. Slobodskaya, Izv. Akad. Nauk SSSR (ser. fiz.) 12, 656 (1948)
- (2) B. I. Stepanov and O. P. Girin, J. Exp. Theor. Phys. USSR 20, 947
(1950)
- (3) Schwartz, Slawsky, and Herzfeld, J. Chem. Phys. 20, 1591 (1952)
Schwartz and Herzfeld, J. Chem. Phys. 22, 767 (1954)
- (4) D. F. Eggers, Jr. and B. L. Crawford, Jr., J. Chem. Phys. 19, 1554
(1951)
- (5) Thorndike, Wells, and Wilson, J. Chem. Phys. 15, 157 (1947)

OFFICE OF NAVAL RESEARCH
PHYSICS BRANCH
TECHNICAL REPORTS DISTRIBUTION LIST
for
NR 019-130

A. Government Distribution

1. Department of Defense

Asst. Sec. of Defense for Research and Development
Information Office Library Branch
Pentagon Building
Washington 25, D.C. (2 copies)

Armed Services Technical Information Agency
Documents Service Center
Knott Building
Dayton 2, Ohio (5 copies)

2. Department of the Navy

Chief, Bureau of Aeronautics
TD-4
Navy Department
Washington 25, D.C.

Chief, Bureau of Ordnance
Rea
Navy Department
Washington 25, D. C.

Chief, Bureau of Ships
Code 300
Navy Department
Washington 25, D.C.

Chief of Naval Research
Office of Naval Research
Washington 25, D.C.
Attn: Physics Branch (Code 421) (3 copies)

Director,
Naval Research Laboratory
Technical Information Officer (Code 2000) (6 Copies)
Code 2021 (2 copies)
Washington 25, D.C.

Commanding Officer
Office of Naval Research Branch Office
150 Causeway Street
Boston 14, Massachusetts

Commanding Officer
Office of Naval Research Branch Office
346 Broadway
New York 13, New York

Commanding Officer
Office of Naval Research Branch Office
86 East Randolph Street
Chicago 1, Illinois

Office of Naval Research Branch Office
Commanding Officer
100 Geary Street
San Francisco 9, California

Commanding Officer
Office of Naval Research Branch Office
1030 East Green Street
Pasadena 1, California

Commanding Officer
Office of Naval Research London Branch Office
Navy #100
Fleet Post Office
New York, New York (2 Copies)

Librarian
U.S. Naval Post Graduate School
Monterey, California

Physics Department
U.S. Naval Post Graduate School
Monterey, California

U.S. Naval Electronics Laboratory Library
San Diego 52, California

Commanding Officer
U.S. Naval War College
Newport, Rhode Island

Director
Physics Research
Naval Ordnance Laboratory
White Oaks, Maryland

Commanding Officer
Physics Division
Naval Ordnance Test Station
Inyokern
China Lake, California

3. Department of the Air Force

Commanding General
Air Research and Development Command
Attn: Office of Scientific Research
Post Office Box 1395
Baltimore 3, Maryland

Air Force Cambridge Research Center
230 Albany Street
Cambridge, Massachusetts
Attn: Physics Branch

4. Department of the Army

Commanding Officer
Frankford Arsenal
Philadelphia 37, Pa.
Attn: Librarian

Commanding Officer
Engineering Research & Development Laboratories
Fort Belvoir, Virginia
Attn: Technical Intelligence Branch

Office of Ordnance Research
Box CM, Duke Station
Durham, North Carolina (2 copies)

Signal Corps Engineering Laboratory
Fort Monmouth, New Jersey
Attn: Technical Information Officer

5. Department of Commerce

Office of Technical Services
Technical Reports Section
Department of Commerce
Washington 25, D.C. (2 copies)

Director
National Bureau of Standards
Washington 25, D.C.

Director
National Bureau of Standards
Carona, California

6. Other Agencies

National Research Council
Division of Physical Sciences
National Academy of Sciences
Washington, D.C.

Director
National Science Foundation
Washington 25, D.C.

U.S. Atomic Energy Commission
Technical Information Service
P.O. Box 62
Oak Ridge, Tennessee

Atomic Energy Commission
Washington 25, D.C.

ATOMS AND MOLECULES REPORTS DISTRIBUTION LIST

Government Contractors

Professor G.B.B.M. Sutherland
Department of Physics
University of Michigan
Ann Arbor, Michigan

Professor S.S. Penner
Department of Physics
California Institute of Technology
Pasadena, California

Dr. W. S. Benedict
The Johns Hopkins University
Baltimore, Maryland

Professor M. Kasha
The Florida State University
Department of Physics
Tallahassee, Florida

Dr. S. Silverman
Applied Physics Laboratory
Johns Hopkins University
Silver Spring, Maryland

Dr. R. S. Mulliken
The University of Chicago
Chicago, Illinois

Dr. D. F. Hornig
Department of Physics
Brown University
Providence, Rhode Island

Professor R. C. Lord
Spectroscopy Laboratory
Massachusetts Institute of Technology
Cambridge 38, Massachusetts

Dr. Bryce L. Crawford, Jr.
Department of Physics
University of Minnesota
Minneapolis, Minnesota

Professor E. B. Wilson, Jr.
Department of Physics
Harvard University
Cambridge, Massachusetts

Dr. H. Sponer
Department of Physics
Duke University
Durham, North Carolina

Professor J. L. Mack
Department of Physics
University of Wisconsin
Madison 6, Wisconsin

Professor C. Beck
Department of Physics
Catholic University
Washington D.C.

Professor J. R. Holmes
Department of Physics
University of Southern California
Los Angeles, California

Professor D. M. Rank
Department of Physics
Pennsylvania State College
State College, Pennsylvania

Professor Leo Goldberg
Department of Physics
University of Michigan
Ann Arbor, Michigan

Professor C. P. Smyth
Department of Physics
Princeton University
Princeton, New Jersey

Dr. N. C. Baenziger
Department of Physics
State University of Iowa
Iowa City, Iowa

Professor Paul C. Cross
Department of Physics
University of Washington
Seattle 5, Washington

Professor T. H. Nielsen
Department of Physics
The Ohio State University Research Foundation
Columbus, Ohio

Dr. K. W. Meissner
Department of Physics
Purdue University
LaFayette, Indiana

Professor Robert B. King
Department of Physics
California Institute of Technology
Pasadena, California

Dr. J. C. Decius
Department of Physics
Oregon State College
Corvallis, Oregon